

App. No. 09/842573
Office Action Dated July 13, 2004
Amd. Dated October 13, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Claim 2 is canceled without prejudice or disclaimer.

Claims 1 and 10 are amended.

Listing of Claims:

1. (Currently Amended) A battery assembly comprising:
a plurality of battery modules electrically connected together, each battery module acting as a secondary battery and comprising:
a plurality of cells, each cell having an electrode group and an electrolyte,
a single container in which the plurality of cells is housed, wherein the container comprises resin and each battery module includes partitions between the cells, and
a single safety valve operating in accordance with an internal pressure of the container,
wherein a working pressure of each safety valve is set so that the safety valve of at least one battery module is opened when the at least one battery module has its maximum internal pressure or less during charge equalization, and
the working pressure of each safety valve is set so that a change in a battery assembly weight after the charge equalization is 0.015 g or less per ampere-hour capacity.
2. (Canceled)

App. No. 09/842573

Office Action Dated July 13, 2004

Amd. Dated October 13, 2004

3. (Original) The battery assembly according to claim 1, wherein the working pressure of each safety valve is set to 0.3 to 0.8 MPa under temperature conditions of 20 to 60°C.

4. (Original) The battery assembly according to claim 1, wherein each battery module comprises a plurality of cells electrically connected together.

5. (Original) The battery assembly according to claim 4, wherein each battery module comprises 2 to 10 cells.

6. (Original) The battery assembly according to claim 1, comprising 20 to 50 battery modules.

7-8 (Canceled)

9. (Original) The battery assembly according to claim 1, wherein each battery module comprises a plurality of cells electrically connected together, and a battery capacity of the battery assembly is 6.5 to 7.2 ampere-hour per cell.

10. (Currently Amended) The battery assembly according to claim 1, wherein the battery assembly ~~is used~~ is configured as a driving power source ~~[[of]]~~ for a vehicle.

11-18 (Canceled)